
5th Wheel Towing Capacity Chart

*5th Wheel
Towing
Capacity
Chart*

*Downloaded from
chat.gizadeathstar.com
by Shyanne Weaver*

INTRODUCTION: WHY A 5TH WHEEL TOWING CAPACITY CHART MATTERS

Pulling a large fifth wheel trailer is a serious undertaking that demands precision, preparation, and a deep understanding of your truck's limits. Unlike conventional bumper-pull trailers, fifth wheel trailers place a significant portion of their weight directly over the truck's rear axle, which changes how towing capacity is calculated and applied.

This is where a **5th wheel towing capacity chart** becomes an indispensable tool. Such a chart consolidates manufacturer ratings, axle configurations, engine options, and transmission choices into a single reference point, helping you avoid the dangerous pitfalls of overloading. Whether you are a seasoned full-timer or a first-time fifth wheel buyer, interpreting these charts correctly is the first step toward safe, confident towing. In this article, we will break down every

aspect of a 5th wheel towing capacity chart, explain how to read one, and provide practical tips to match your truck with the ideal fifth wheel trailer.

UNDERSTANDING THE BASICS OF FIFTH WHEEL TOWING

What Is Towing Capacity?

Towing capacity, often called the **tow rating**, is the maximum weight a vehicle can pull behind it. For fifth wheel towing, this rating is typically higher than for conventional trailers because the hitch distributes weight more favorably.

However, it is not the only number you need to consider. A **5th wheel towing capacity chart** usually lists the maximum trailer weight (MTW) the manufacturer has certified for a specific truck model, engine, axle ratio, and cab configuration.

Exceeding this number can strain the drivetrain, brakes, and suspension, leading to catastrophic failure on the road.

Key Terms You Must Know

To fully understand a fifth wheel towing chart, you should be familiar with these

terms:

- **Gross Vehicle Weight Rating (GVWR):**

The maximum total weight of your truck, including passengers, cargo, fuel, and the tongue weight of the trailer.

- **Gross Combined Weight Rating (GCWR):**

The maximum weight of your fully loaded truck and trailer combined. This is the ultimate upper limit.

- **Pin Weight:** The portion of the fifth wheel trailer's weight that bears down on the hitch. Typically 15–25% of the trailer's GVWR. Pin

weight counts toward the truck's payload, not just its towing capacity.

- **Payload**

Capacity: The amount of weight your truck can carry in its cab and bed, including the pin weight of the fifth wheel. This is often the limiting factor for fifth wheel towing, not the tow rating itself.

- **Curb Weight:**

The weight of the truck with a full tank of fuel and all fluids, but without passengers or cargo. Subtract curb weight from GVWR to find available payload.

HOW TO READ A 5TH WHEEL TOWING CAPACITY CHART

A typical chart organizes data by truck model, engine, drivetrain, and axle ratio. For example, a chart might list a 2024 Ford F-350 with the 6.7L Power Stroke diesel, 4.30 axle ratio, and dual rear wheels as having a maximum fifth wheel towing capacity of 32,000 pounds. But that number assumes a base curb weight with a 150-pound driver and no additional options. Add a heavy tool box, a tonneau cover, a second passenger, or aftermarket accessories, and your effective capacity drops.

Columns You'll Commonl y See

- **Model / Trim:** Different trims (XL, XLT, Lariat, etc.) have varying base weights.
- **Engine:** Diesel engines usually offer higher tow ratings than gasoline, but they also add weight.
- **Axle Ratio:** A numerically higher ratio (e.g., 4.30 vs. 3.73) increases pulling power and towing capacity, though it may reduce fuel

YOUR TRUCK.

- **Drive Type:**
4×4 models weigh more than 4×2, reducing payload and towing capacity slightly.
- **Wheelbase / Cab Configuration:**
Crew cabs and long beds can affect weight distribution but usually have similar capacities to regular cabs.
- **Max Fifth Wheel Towing:**
The maximum trailer weight you can safely pull, assuming the trailer's pin weight does not exceed the truck's payload.

KEY FACTORS THAT INFLUENCE

TOWING CAPACITY

The Role of Payload

Many truck owners focus only on the tow rating and forget about payload. For fifth wheel towing, payload is often the bottleneck. If your truck has a payload capacity of 3,000 pounds and the fifth wheel's pin weight is 2,500 pounds when loaded, you only have 500 pounds left for passengers, luggage, and any gear in the truck bed. A **5th wheel towing capacity chart** usually lists the trailer weight for a base vehicle, so you must subtract the pin weight from your

specific payload. Use the chart as a starting point, then do the math with your actual truck and trailer weights.

Hitch and Equipment

The type of fifth wheel hitch you install also affects capacity. Sliding hitches, which allow sharp turns in short-bed trucks, can add 150-250 pounds to the pin weight. Likewise, heavy under-bed mounting kits or rails contribute to the truck's curb weight, reducing available payload. Always factor in the hitch weight when consulting a chart.

Terrain and Driving Conditions

Manufacturer ratings assume ideal conditions: flat, paved roads at sea level, moderate temperatures, and no wind. If you plan to tow through mountain passes, on dirt roads, or in hot desert climates, derate your capacity by 10-20%. The chart cannot account for every scenario, so use a safety margin.

SAMPLE 5TH WHEEL TOWING

CAPACITY DATA	
(ILLUSTRATIVE EXAMPLES)	With 4.30 axle, but payload limits may reduce usable trailer weight.
	• F-450 DRW 6.7L Diesel: Up to 32,000 lbs, typical for very large fifth wheels.
Ford F-Series (2023–2024)	Ram 2500 / 3500
	• Ram 2500 6.4L Gas: Max 5th wheel towing around 14,000–16,000 lbs. • Ram 3500 SRW 6.7L Cummins: Up to 24,000–26,000 lbs depending on cab and axle. • Ram 3500 DRW
	• F-250 6.8L Gas: Max 5th wheel towing approx. 14,000–18,000 lbs (varies by axle ratio). • F-350 SRW 6.7L Diesel: Up to 29,000 lbs

6.7L Cummins:

Up to 35,100 lbs
with the
high-output
engine.

Chevrolet Silverado / GMC Sierra

- **2500HD 6.6L**
Gas: Max 5th
wheel towing
~17,000–19,000
lbs.
- **3500HD 6.6L**
Duramax DRW:
Up to 31,500 lbs
(with specific
configuration).

Note: These are approximate. The official **5th wheel towing capacity chart** for each model year contains precise

numbers used by
dealers and RV owners.

HOW TO MATCH YOUR TRUCK WITH A FIFTH WHEEL USING THE CHART

Step 1: Determin e Your Truck's Wet and Weighed Payload

Take your truck to a certified scale with a full tank of fuel, all passengers, and your typical gear. Subtract the measured weight from the GVWR listed on the driver's door

sticker. This is your actual available payload.

Step 2: Find the Unloaded Pin Weight of the Trailer

Manufacturers list a dry pin weight for each fifth wheel. Add about 20% of the trailer's cargo capacity to estimate the loaded pin weight. Use the chart to confirm that the loaded pin weight does not exceed your available payload.

Step 3: Cross-Ref erence with the Towing Capacity Chart

Look up your exact truck configuration on the chart. The listed "Max Fifth Wheel Towing" assumes a pin weight at the 15-25% range. If your trailer's loaded weight is within that number, you are likely within the tow rating. But remember: the towing capacity chart does not replace payload verification.

Step 4: Account for a Safety Margin

Even if the numbers line up perfectly, leave at least 10% headroom in both payload and towing capacity. This cushions you against scale errors, aftermarket accessories, and varying road conditions.

COMMON MISTAKES WHEN INTERPRETING A 5TH WHEEL TOWING CAPACITY CHART

- **Mistaking**

GVWR for

Payload: GVWR is the maximum total weight, not what you can add. Payload is GVWR minus curb weight.

- **Using the Dry Weight Instead of GVWR of the Trailer:**

The chart relates to the trailer's gross weight, not its empty weight. You must consider water, propane, food, and personal belongings.

- **Ignoring the Effect of**

Options: A sunroof, larger fuel tank, or adaptive cruise control might increase curb weight by 200 pounds or more, eating into

payload.

- **Assuming All Trucks of the Same Model Have the Same Capacity:** Cab length, bed length, and even tire size can change the numbers. Always check the chart for your unique vehicle identification number (VIN).

WHY REAL-WORLD TOWING DIFFERS FROM CHART NUMBERS

Manufacturers test trucks under controlled laboratory conditions. They use a 150-pound driver, no cargo, and standard equipment. In reality, you may have a family of four, a loaded truck bed, a tonneau cover, a tool box, and a

heavy hitch. All of these subtract from the margin. A **5th wheel towing capacity chart** is a best-case scenario; you must derate it for your actual load. Additionally, wind resistance, high altitude, and steep grades can reduce engine power and braking effectiveness. Many experienced RVers recommend staying at 80% or less of the chart's maximum.

TOOLS AND RESOURCES TO COMPLEMENT THE CHART

- **Truck Manufacturer's Towing Guides:** Ford, Ram, and GM each provide detailed downloadable

PDFs with specific charts for every model year.

- **Fifth Wheel Manufacturers' Spec Sheets:**

They list unloaded pin weight, dry weight, and GVWR. Compare these directly to the chart.

- **Online Payload Calculators:**

Several websites let you input your truck's

sticker values and estimate your safe towing capacity.

- **Public Truck Scales:** Weigh your rig fully loaded to confirm you are within limits. This is the only way to be 100% sure.

**CONCLUSION:
NAVIGATE WITH
CONFIDENCE
USING THE RIGHT
CHART**

A